

薄型交流電壓, 電流隔離傳送器

(SLIM TYPE AC CURRENT/VOLTAGE ISOLATED TRANSMITTER)

MODEL
STA



■特點(FEATURES)

- 精確度0.1%滿刻度(TRMS),0.25%滿刻度(RMS) (Accuracy 0.1%F.S.(TRMS),0.25%(RMS))
- 多種輸入輸出選擇(Wide selection of input/output range)
- 輸入/輸出1/輸出2絕緣耐壓 1.5仟伏特/1分鐘(Dielectric strength 1.5KVac/1 min.(input/output1/output2))
- 寬範圍交直流兩用電源設計(Wide input range for auxiliary power)
- 尺寸小,穩定性高(Dimension small & High stability)

1.MODEL:STA-□ □ □ □ □


(選購型號)

NO	Input Type	NO	Input Range	NO	Input Range	NO	Output 1 Range	NO	Output 2 Range	NO	Aux. Power
A	Voltage(RMS)	1	AC0~36V	6	AC0~1A	C	1~5V	N	None	A	AC/DC 18~60V
B	Voltage(TRMS)	2	AC0~110V	7	AC0~5A	D	0~10V	C	1~5V	B	AC/DC 90~260V
C	Current(RMS)	3	AC0~150V	9	SPECIFIED	F	0~1mA	D	0~10V		• Less 4VA for AC/DC input
D	Current(TRMS)	4	AC0~220V			I	4~20mA	I	4~20mA		
		5	AC0~300V			R	SPECIFIED	R	SPECIFIED		

2.SPCIFICATION (主要規格)

- Measuring accuracy (精確度) : 0.1% F.S. (TRMS), 0.25% F.S. (RMS)
- Input burden (輸入負載) : <0.2VA (ACV), <0.25VA (ACA)
- Input frequency (輸入頻率) : AC40~70Hz
- Maximum input over (最大過載能力) : Current related input: 3 x rated continuous, 10 x rated 30 sec., 25 x rated 3 sec., 50 x rated 1 sec.; Voltage related input: maximum 2 x rated continuous
- Response time (輸出反應時間) : <250ms (0~90%)
- Output drive capability (輸出負載能力) : <10mA for voltage mode, <10V for current mode
- Output ripple(p-p) (輸出漣波) : <0.1% F.S.
- Zero (offset) range (歸零調整範圍) : 0~±5% F.S.
- Span (scale) range (最大值調整範圍) : 0~±10% F.S.
- Temp. coefficient (溫度係數) : 100ppm/°C (0~50°C)
- Isolation (隔離特性) : Input/Output1/Output2/Power/Case
- Insulation Resistance (絕緣阻抗) : >100M ohm with 500V DC
- Dielectric strength (絕緣耐壓能力) : 1.5KVac/1 min. (input/Output1/Output2/power), 1200Vdc (input/Output1/Output2)
- Operating condition (使用環境條件) : 0~60°C (20 to 90% RH non-condensed)
- Storage condition (存放環境條件) : 0~70°C (20 to 90% RH non-condensed)
- Construction (安裝方式) : 35mm DIN rail (EN50022)
- CE EMC Certification (CE 認證) : EN 55022:1998/A1:2000 Class A, EN 61000-3-2:2000, EN 61000-3-3:1995/A1:2001, EN 55024:1998/A1:2001

3.TERMINAL CONNECTION (接線圖)



4.DIMENSION (unit:mm) (外型尺寸)

